

S P E C I F I C A T I O N P R O P O S A L

Description	Weight Front	Weight Rear
Price Level		
WST 47X/49X PRL-28X (EFF:MY25 ORDERS)		
Data Version		
SPECPRO21 DATA RELEASE VER 040		
Vehicle Configuration		
WESTERN STAR 47X	9,050	6,525
2025 MODEL YEAR SPECIFIED		
SET BACK AXLE - TRUCK		
TRAILER TOWING PROVISION AT END OF FRAME WITH SAE J560	10	10
LH PRIMARY STEERING LOCATION		
General Service		
TRUCK/TRAILER CONFIGURATION		
DOMICILED, USA 50 STATES (INCLUDING CALIFORNIA AND CARB OPT-IN STATES)		
CARB CLEAN IDLE LABELS NOT FOR INITIAL REGISTRATION IN STATES REQUIRING CARB EMISSIONS CERTIFICATION (INCLUDES 6X4 INCH LABELS ON LOWER FORWARD OF DRIVER DOOR)		
NONE		
CONSTRUCTION SERVICE		
GOVERNMENT BUSINESS SEGMENT		
DIRT/SAND/ROCK COMMODITY		
TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN TRANSIT, IS SPENT ON PAVED ROADS.		
MAXIMUM 8% EXPECTED GRADE		
SMOOTH CONCRETE OR ASPHALT PAVEMENT - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE		

Description	Weight Front	Weight Rear
WESTERN STAR VOCATIONAL WARRANTY		
EXPECTED FRONT AXLE(S) LOAD : 12000.0 lbs		
EXPECTED REAR DRIVE AXLE(S) LOAD : 40000.0 lbs		
EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 52000.0 lbs		
EXPECTED GROSS COMBINATION WEIGHT : 80000.0 lbs		
Truck Service		
END DUMP BODY		
TRUCK BODY CORPORATION		
Tractor Service		
FLATBED TRAILER		
SINGLE (1) TRAILER		
Engine		
CUM L9 370 HP @ 2100 RPM; 2100 GOV RPM, 1250 LB-FT @ 1200 RPM	-850	-70
Electronic Parameters		
75 MPH ROAD SPEED LIMIT		
CRUISE CONTROL SPEED LIMIT SAME AS ROAD SPEED LIMIT		
10 MINUTE IDLE SHUTDOWN - CONTINUOUS OVERRIDE WITH CLUTCH AND SERVICE BRAKE		
PTO MODE ENGINE RPM LIMIT - 900 RPM		
PTO MODE BRAKE OVERRIDE - SERVICE BRAKE APPLIED		
PTO RPM WITH CRUISE SET SWITCH - 800 RPM		
PTO RPM WITH CRUISE RESUME SWITCH - 900 RPM		
PTO MODE CANCEL VEHICLE SPEED - 5 MPH		
PTO GOVERNOR RAMP RATE - 250 RPM PER SECOND		
FUEL DOSING OF AFTERTREATMENT ENABLED IN PTO MODE-CLEANS HYDROCARBONS AT HIGH TEMPERATURES ONLY		
ONE TEM PTO SPEED		
PTO SPEED 1 SETTING - 900 RPM		
NO FLEET SPEC FOR PARAMETERIZATION		
PTO MINIMUM RPM - 700		
REGEN INHIBIT SPEED THRESHOLD - 5 MPH		

Description	Weight Front	Weight Rear
PTO 1, WITH SWITCH, TEM SUPPLIED REQUEST AND INTERLOCKS, WITH PTO CONNECTIONS, STATIONARY INTERLOCKS		
Engine Equipment		
EPA 2010 GHG 2024/CARB 2024 ULTRALOW NOX CONFIGURATION		
STANDARD OIL PAN		
ENGINE MOUNTED OIL CHECK AND FILL		
SIDE OF HOOD AIR INTAKE WITH ENGINE MOUNTED AIR CLEANER		
DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE	-10	
(2) DTNA GENUINE, FLOODED STARTING, MIN 2000CCA, 370RC, THREADED STUD BATTERIES	-50	-20
BATTERY BOX WITH ALUMINUM COVER MOUNTED SHORT SIDE TO RAIL	-50	10
SINGLE BATTERY BOX FRAME MOUNTED LH SIDE BACK OF CAB		
WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN		
UNPOLISHED ALUMINUM WST BATTERY BOX COVER		
AUXILIARY POWER NET DISTRIBUTION BLOCK FOR BODY BUILDER USE	5	
POSITIVE AND NEGATIVE POSTS FOR JUMPSTART LOCATED ON FRAME NEXT TO STARTER	2	
CUMMINS TURBOCHARGED 18.7 CFM AIR COMPRESSOR WITH INTERNAL SAFETY VALVE		
ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM		
C-BRAKE BY JACOBS WITH LOW/OFF/HIGH BRAKING DASH SWITCH		
RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH HORIZONTAL TAILPIPE	-30	-20
ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWITCH		
STANDARD EXHAUST SYSTEM LENGTH		
RH STANDARD HORIZONTAL TAILPIPE		
13 GALLON DIESEL EXHAUST FLUID TANK	9	3

Description	Weight Front	Weight Rear
UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER		
LH HEAVY DUTY STANDARD DIESEL EXHAUST FLUID TANK LOCATION		
STANDARD DIESEL EXHAUST FLUID TANK CAP		
AIR POWERED ON/OFF ENGINE FAN CLUTCH		
AUTOMATIC FAN CONTROL WITHOUT DASH SWITCH, NON ENGINE MOUNTED		
DETROIT FUEL/WATER SEPARATOR WITH WATER IN FUEL SENSOR AND 12 VOLT PREHEATER	10	
CUMMINS SPIN ON FUEL FILTER		
COMBINATION FULL FLOW/BYPASS OIL FILTER		
1400 SQUARE INCH VOCATIONAL RADIATOR		
ANTIFREEZE TO -34F, OAT (NITRITE AND SILICATE FREE) EXTENDED LIFE COOLANT		
GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT		
STANDARD CHARGE AIR COOLER PLUMBING		
RADIATOR DRAIN VALVE		
LOWER RADIATOR GUARD		
PHILLIPS-TEMRO 1000 WATT/115 VOLT BLOCK HEATER	4	
CHROME ENGINE HEATER RECEPTACLE MOUNTED UNDER LH DOOR		
ELECTRIC GRID AIR INTAKE WARMER		
DELCO 12V 39MT HD/OCP STARTER WITH THERMAL PROTECTION AND INTEGRATED MAGNETIC SWITCH	-45	

Transmission

ALLISON 3000 RDS AUTOMATIC TRANSMISSION WITH PTO PROVISION	-230	-130
---	------	------

Transmission Equipment

ALLISON VOCATIONAL PACKAGE 223 -
AVAILABLE ON 3000/4000 PRODUCT FAMILIES
WITH VOCATIONAL MODELS RDS, HS, MH AND
TRV

ALLISON VOCATIONAL RATING FOR ON/OFF
HIGHWAY APPLICATIONS AVAILABLE WITH ALL
PRODUCT FAMILIES

PRIMARY MODE GEARS, LOWEST GEAR 1,
START GEAR 1, HIGHEST GEAR 6, AVAILABLE
FOR 3000/4000 PRODUCT FAMILIES ONLY

Description	Weight Front	Weight Rear
SECONDARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY		
PRIMARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		
SECONDARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		
PRIMARY SHIFT SPEED RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		
SECONDARY SHIFT SPEED RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		
FUEL SENSE 2.0 DISABLED - PERFORMANCE - TABLE BASED		
NO TCU-PTO DRIVE INTERFACE		
DIRECTION CHANGE ENABLED WITH MULTIPLEXED SERVICE BRAKES - ALLISON 5TH GEN TRANSMISSIONS		
ELECTRONIC TRANSMISSION WIRING TO CUSTOMER INTERFACE CONNECTOR		
CUSTOMER INSTALLED CHELSEA 280 SERIES PTO		
PTO MOUNTING, LH SIDE OF MAIN TRANSMISSION ALLISON		
MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION DRAIN, AXLE(S) FILL AND DRAIN		
PUSH BUTTON ELECTRONIC SHIFT CONTROL, DASH MOUNTED		
WATER TO OIL TRANSMISSION COOLER		
TRANSMISSION OIL CHECK AND FILL WITH ELECTRONIC OIL LEVEL CHECK		
SYNTHETIC TRANSMISSION FLUID (TES-295 COMPLIANT)		

Front Axle and Equipment

CUMMINS-MERITOR MFS-12-143A 12,000# FF1
71.5 INCH KPI/3.74 INCH DROP SINGLE FRONT
AXLE

CONMET PRESET PLUS PREMIUM IRON FRONT
HUBS 20

Description	Weight Front	Weight Rear
MERITOR 16.5X5 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES	-10	
NON-ASBESTOS FRONT BRAKE LINING		
CONMET CAST IRON FRONT BRAKE DRUMS		
NO FRONT BRAKE DUST SHIELDS		
FRONT OIL SEALS		
VENTED FRONT HUB CAPS WITH WINDOW, CENTER AND SIDE PLUGS - OIL		
MERITOR AUTOMATIC FRONT SLACK ADJUSTERS		
SINGLE POWER STEERING GEAR, BENDIX, 12-13.3K		
2 QUART SEE THROUGH POWER STEERING RESERVOIR		
MINERAL SAE 80/90 FRONT AXLE LUBE		
Front Suspension		
12,000# DUAL TAPERLEAF FRONT SUSPENSION		
MAINTENANCE FREE RUBBER BUSHINGS - FRONT SUSPENSION		
FRONT SHOCK ABSORBERS		
Rear Axle and Equipment		
CUMMINS-MERITOR MT-40-14X 40,000# R-SERIES TANDEM REAR AXLE		10
CONMET PRESET PLUS PREMIUM IRON REAR HUBS		60
5.29 REAR AXLE RATIO		
IRON REAR AXLE CARRIER WITH OPTIONAL HEAVY DUTY AXLE HOUSING		40
MXL 176T MERITOR EXTENDED LUBE MAIN DRIVELINE WITH HALF ROUND YOKES	-50	-50
MXL 17T MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH HALF ROUND YOKES		
(1) INTERAXLE LOCK VALVE FOR TANDEM DRIVE AXLES		
INDICATOR LIGHT FOR EACH INTERAXLE LOCKOUT SWITCH		
MERITOR 16.5X7 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES		175
NON-ASBESTOS REAR BRAKE LINING		

Description	Weight Front	Weight Rear
ASPHALT SPREADER CLEARANCE REAR BRAKE GEOMETRY		
CONMET CAST IRON REAR BRAKE DRUMS		
REAR BRAKE DUST SHIELDS		10
REAR OIL SEALS		
WABCO TRISTOP D LONGSTROKE 2-DRIVE AXLE SPRING PARKING CHAMBERS		
HALDEX AUTOMATIC REAR SLACK ADJUSTERS		
CURRENT AVAILABLE SYNTHETIC 75W-90 REAR AXLE LUBE		
STANDARD REAR AXLE BREATHER(S)		
Rear Suspension		
TUFTRAC GEN2 40,000# REAR SPRING SUSPENSION		410
9.5 INCH NOMINAL RIDE HEIGHT (460MM GLOBAL REFERENCE HEIGHT)		
AXLE CLAMPING GROUP		
55 INCH AXLE SPACING		
FORE/AFT AND TRANSVERSE CONTROL RODS		
REAR SHOCK ABSORBERS - ONE AXLE		
Pusher / Tag Equipment		
NO PUSHER/TAG BRAKE DUST SHIELDS		
Brake System		
WABCO 4S/4M ABS WITH TRACTION CONTROL WITH ATC SHUT OFF SWITCH		
REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID CHASSIS AIR LINES		
RELAY VALVE WITH 5-8 PSI CRACK PRESSURE, NO REAR PROPORTIONING VALVE		
WABCO SYSTEM SAVER 1200 HEATED AIR DRYER WITH PRESSURE CONTROL VALVE		
WABCO OIL COALESCING FILTER FOR AIR DRYER		
AIR DRYER MOUNTED UNDER HOOD		
STEEL AIR BRAKE RESERVOIRS		
PULL CABLES ON ALL AIR RESERVOIR(S)		
Trailer Connections		
AIR CONNECTIONS TO END OF FRAME WITH GLAD HANDS FOR TRUCK AND NO DUST COVERS	5	5

Description	Weight Front	Weight Rear
PRIMARY CONNECTOR/RECEPTACLE WIRED FOR SEPARATE STOP/TURN, ABS CENTER PIN POWERED THROUGH IGNITION		
SAE J560 7-WAY PRIMARY TRAILER CABLE RECEPTACLE MOUNTED END OF FRAME		

Wheelbase & Frame

4475MM (176 INCH) WHEELBASE		
9.0MM X 83.0MM X 283.0MM STEEL FRAME (0.35X3.35X11.14 INCH) 120 KSI	-210	140
1625MM (64 INCH) REAR FRAME OVERHANG		
FRAME OVERHANG RANGE: 61 INCH TO 70 INCH	-20	60
CALC'D BACK OF CAB TO REAR SUSP C/L (CA) : 111.02 in		
CALC'D FRAME LENGTH - OVERALL : 285.34 in		
FRAME HEIGHT TOP FRONT UNLADEN : 32.83 in		
FRAME HEIGHT TOP FRONT LADEN : 30.64 in		
FRAME HEIGHT TOP REAR UNLADEN : 42.74 in		
FRAME HEIGHT TOP REAR LADEN : 40.33 in		
SQUARE END OF FRAME		
STANDARD WEIGHT ENGINE CROSSMEMBER		
STANDARD CAST ALUMINUM CROSSMEMBER BACK OF TRANSMISSION		
STANDARD CAST ALUMINUM MIDSHIP		
STANDARD CAST ALUMINUM REARMOST CROSSMEMBER		
STANDARD SUSPENSION CROSSMEMBER		20
CAST ALUMINUM REAR SUSPENSION CROSSMEMBER		

Chassis Equipment

UNPOLISHED ALUMINUM WST EQUIPMENT COVERS		
BRIGHT STEEL 1/8 INCH VOCATIONAL BUMPER		
REMOVABLE FRONT TOW/RECOVERY DEVICE, STORED ON CHASSIS FRAME		
BUMPER MOUNTING FOR SINGLE LICENSE PLATE		
HUCK-SPIN ROUND COLLAR CHASSIS FASTENERS		
EXTERIOR HARNESES WRAPPED IN ABRASION TAPE		

Fuel Tanks

Description	Weight Front	Weight Rear
100 GALLON/378 LITER ALUMINUM FUEL TANK - LH	10	10
25 INCH DIAMETER FUEL TANK(S) PLAIN ALUMINUM/PAINTED STEEL FUEL/HYDRAULIC TANK(S) WITH PAINTED BANDS FUEL TANK(S) FORWARD PLAIN STEP FINISH FUEL TANK CAP(S) EQUIFLO INBOARD FUEL SYSTEM HIGH TEMPERATURE REINFORCED NYLON FUEL LINE		
Tires		
CONTINENTAL HSR3 11R22.5 14 PLY RADIAL FRONT TIRES	70	
CONTINENTAL HDL2 11R22.5 14 PLY RADIAL REAR TIRES		88
Wheels		
MAXION WHEELS 91262 22.5X8.25 10-HUB PILOT 6.20 INSET 5-HAND STEEL DISC FRONT WHEELS	10	
MAXION WHEELS 91262 22.5X8.25 10-HUB PILOT 5-HAND STEEL DISC REAR WHEELS FRONT WHEEL MOUNTING NUTS REAR WHEEL MOUNTING NUTS		40
Cab Exterior		
111.6 INCH BBC CONVENTIONAL ALUMINUM CAB PAINTED CAB ACCENT MOLDING FRONT FENDERS INTERIOR GRAB HANDLES WITH ADDED LOWER LH AND RH A PILLAR GRAB HANDLES AND LH AND RH EXTERIOR NON-SLIP GRAB HANDLES BRIGHT HOOD MOUNTED AIR INTAKE GRILLE, BLACK SCREEN X-SERIES STEEL REINFORCED ALUMINUM CAB X-SERIES VOCATIONAL HOOD HOOD OPENING ASSIST WITH LOCKING STRUT WESTERN STAR NAMEPLATES DUAL HADLEY SD-978 26 INCH RECTANGULAR AIR HORNS		

Description	Weight Front	Weight Rear
DUAL ELECTRIC HORNS		
REAR LICENSE PLATE MOUNT END OF FRAME		
DUAL STAGE INTELLIGENT LED HEADLIGHTS WITH HEATED LENS SYSTEM		
ROOF MOUNTED LED MARKER LIGHTS		
DAYTIME RUNNING LIGHTS WITH ROCKER/TOGGLE MOMENTARY INTERRUPTER SWITCH		
INTEGRAL LED STOP/TAIL/BACKUP LIGHTS		
LED SIDE TURN SIGNAL		
C-BAR MIRROR SYSTEM WITH DUAL HEATED MIRRORS WITH INTEGRAL HEATED CONVEX, DUAL REMOTE, STAINLESS STEEL BACK COVER, AND BLACK C-BAR		
102 INCH EQUIPMENT WIDTH		
LH AND RH CONVEX MIRRORS INTEGRAL WITH PRIMARY MIRRORS		
RH DOWN VIEW MIRROR		
RH AND LH HEATED BLACK HOOD/FENDER MOUNTED SIDE VIEW MIRRORS WITH BRIGHT FINISH MOUNTING ARM	8	
STANDARD SIDE/REAR REFLECTORS		
UNPOLISHED ALUMINUM WST AFTERTREATMENT SYSTEM COVER		
PARK BRAKE REMINDER WARNING SYSTEM		
HIGH VISIBILITY 3-PIECE SOLAR TINTED REAR WINDOW, (1) 31 INCH X 20 INCH SOLAR TINTED REAR WINDOW, (2) 9 INCH X 20 INCH	20	
1-PIECE ROPED-IN SOLAR GREEN GLASS WINDSHIELD		
8 LITER (2 GAL) WINDSHIELD WASHER RESERVOIR, CAB MOUNTED, WITHOUT FLUID LEVEL INDICATOR		

Cab Interior

X-SERIES BASE INTERIOR TRIM LEVEL
PACKAGE

CHARCOAL BLACK VINYL BASE LEVEL
INTERIOR

CARBON WITH BASE BLACK ACCENT

BLACK MATS

(2) DASH MOUNTED POWER OUTLETS AND
COIN TRAY

FORWARD ROOF MOUNTED CONSOLE

Description	Weight Front	Weight Rear
LH AND RH DOOR STORAGE POCKETS INTEGRATED INTO MOLDED DOOR PANELS		
(2) COAT HOOKS ON BACKWALL OF CAB		
DIGITAL ALARM CLOCK IN DRIVER DISPLAY		
2-1/2 LB. FIRE EXTINGUISHER MOUNTED INBOARD OF DRIVER SEAT	5	
STANDARD HEATER PLUMBING		
RADIATOR MOUNTED AIR CONDITIONER CONDENSER		
STANDARD INSULATION		
STANDARD LED CAB LIGHTING		
NO SECURITY DEVICE		
DOOR LOCKS AND IGNITION SWITCH KEYED THE SAME		
KEY QUANTITY OF 4		
LH AND RH ELECTRIC DOOR LOCKS WITH AUTO UNLOCK FEATURE WHEN DOOR IS SET FROM OPEN TO CLOSED POSITION		
BLACK DOOR HANDLES		
TRIANGULAR REFLECTORS WITHOUT FLARES	10	
BASIC 2.0 HIGH BACK AIR SUSPENSION DRIVER SEAT WITH 1 CHAMBER AIR LUMBAR, INTEGRATED CUSHION EXTENSION AND TILT		
BASIC 2.0 HIGH BACK NON SUSPENSION PASSENGER SEAT		
BLACK SUSPENSION COVER FOR AIR DRIVER SEAT	2	
NO SEAT ARMREST		
BLACK VINYL DRIVER SEAT COVER WITH NO LOGO		
BLACK VINYL PASSENGER SEAT COVER WITH NO LOGO		
3 POINT ADJUSTABLE D-RING RETRACTOR DRIVER AND FIXED D-RING RETRACTOR PASSENGER SEAT BELTS		
ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN		
4-SPOKE 18 INCH (450MM) BLACK STEERING WHEEL WITH SWITCHES		
DRIVER AND PASSENGER INTERIOR SUN VISORS		
Instruments & Controls		
STANDARD FOOT PEDAL SYSTEM		

Description	Weight Front	Weight Rear
ELECTRONIC ACCELERATOR CONTROL		
ENGINE REMOTE INTERFACE WITH PARK BRAKE INTERLOCK		
BLACK GAUGE BEZELS		
STANDARD CENTER INSTRUMENT PANEL		
DUAL NEEDLE PRIMARY AND SECONDARY AIR PRESSURE GAUGE		
INTAKE MOUNTED AIR RESTRICTION INDICATOR WITHOUT GRADUATIONS		
97 DB BACKUP ALARM		3
ELECTRONIC CRUISE CONTROL WITH CONTROLS ON STEERING WHEEL SPOKES		
KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION OFF/RUN/START/ACCESSORY		
PREMIUM INSTRUMENT CLUSTER WITH 5.0 INCH TFT COLOR DISPLAY		
DIGITAL PANEL LAMP DIMMER SWITCH IN DRIVER DISPLAY		
HEAVY DUTY ONBOARD DIAGNOSTICS INTERFACE CONNECTOR LOCATED BELOW LH DASH		
2 INCH ELECTRIC FUEL GAUGE		
ENGINE REMOTE INTERFACE WITH ONE OR MORE SET SPEEDS		
ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE		
NO ENGINE OIL TEMPERATURE GAUGE		
ELECTRIC ENGINE OIL PRESSURE GAUGE		
2 INCH TRANSMISSION OIL TEMPERATURE GAUGE		
ELECTRONIC OUTSIDE TEMPERATURE SENSOR DISPLAY IN DRIVER MESSAGE CENTER		
ENGINE AND TRIP HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY		
PTO CONTROLS FOR ENHANCED VEHICLE ELECTRIC/ELECTRONIC ARCHITECTURE		
NO OBSTACLE DETECTION SYSTEM		
NO SIDE OBJECT DETECTION SYSTEM		
NO REVERSE PROXIMITY SENSOR		
NO DR ASSIST SYSTEM		
NO VEHICLE STABILITY ADVISOR OR CONTROL		
NO LANE DEPARTURE WARNING SYSTEM		

Description	Weight Front	Weight Rear
TMC RP1226 ACCESSORY CONNECTOR LOCATED BEHIND PASSENGER SIDE REMOVEABLE DASH PANEL		
AM/FM/WB WORLD TUNER RADIO WITH AUXILIARY INPUT, J1939		
DASH MOUNTED RADIO		
STANDARD SPEAKER SYSTEM		
NO AM/FM RADIO ANTENNA		
NO SPEAKER/LEAD FOR 2-WAY RADIO		
NO CB ANTENNA, BRACKET OR LEAD		
HEADLINER MULTI-BAND ANTENNA: AM/FM/WEATHERBAND, WIFI/BLUETOOTH, GNSS/GPS		
ELECTRONIC MPH SPEEDOMETER WITH SECONDARY KPH SCALE, WITHOUT ODOMETER		
ELECTRONIC 2500 RPM TACHOMETER		
DETROIT CONNECT PLATFORM HARDWARE		
5 YEARS DAIMLER CONNECTIVITY BASE PACKAGE (FEATURES VARY BY MODEL) POWERED BY DETROIT CONNECT ON CUMMINS ENGINES		
IGNITION SWITCH CONTROLLED ENGINE STOP		
ONE EXTRA HARDWIRED SWITCH IN DASH, ROUTE TO END OF FRAME, BLUNTCUT		
HARDWIRE SWITCH #1, ON/OFF MOMENTARY, 20 AMPS IGNITION POWER		
NO PRE TRIP SYSTEM TEST		
BW TRACTOR PROTECTION VALVE		
TRAILER HAND CONTROL BRAKE VALVE	2	
NO TURBO AIR PRESSURE GAUGE		
DIGITAL VOLTAGE DISPLAY INTEGRAL WITH DRIVER DISPLAY		
ROTARY HEADLAMP SWITCH, MARKER LIGHTS/HEADLIGHTS SWITCH WITH PULL OUT FOR OPTIONAL FOG/ROAD LAMPS		
TWO VALVE PARKING BRAKE SYSTEM WITH WARNING INDICATOR		
SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, HEADLAMP FLASH, WASH/WIPE/INTERMITTENT		
QUICKFIT POWERTRAIN INTERFACE CONNECTOR UNDER CAB WITH CAPS		

Design

	Description	Weight Front	Weight Rear
	PAINT: ONE SOLID COLOR		
Color	CAB COLOR A: L0006EY WHITE ELITE EY BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT POWDER WHITE (N0006EA) FRONT WHEELS/RIMS (PKWHT21, TKWHT21, W, TW) POWDER WHITE (N0006EA) REAR WHEELS/RIMS (PKWHT21, TKWHT21, W, TW)		

Certification / Compliance

U.S. FMVSS CERTIFICATION, EXCEPT SALES CABS AND GLIDER KITS

Secondary Factory Options

- * ENG BRK PRESLECT - DTNA STANDARD ENGINE BRAKE RANGE
- * ALT ENG BRK PRESLECT - DTNA STD ALT ENGINE BRAKE PRESLECT
- * TRANS PROG-ENABLED 2013
- * DRIVER SW INPUT - DEFAULT - NO SWITCHES

T O T A L V E H I C L E S U M M A R Y

Weight Summary

	Weight Front	Weight Rear	Total Weight
Factory Weight*	7697 lbs	7329 lbs	15026 lbs
Total Weight*	7697 lbs	7329 lbs	15026 lbs

Extended Warranty

CUMMINS ENGINE CARB COMPLIANT: L9 HD1 MD DTY 5 YEARS / 200,000 MILES / 322,000 KM EXTENDED WARRANTY. FEX APPLIES
 CUMMINS AFTERTREATMENT CARB22: L9 AT3 MD DTY 5 YEARS / 200,000 MILES / 322,000 KM EXTENDED WARRANTY. FEX APPLIES
 ALLISON 3000 RDS SERIES TRANSMISSION EXTEND WARRANTY, 5 YEARS/UNLIMITED MILES FEX