

Kennel Bid Specifications:

Qty: **Description:**

- 22 FRP (fiberglass reinforced plastic)** isolation panels with Wire 69.375" high x 48" long with 3/4" wide aluminum frame
-with Stainless Steel Wire 24" high
-with FRP (fiberglass reinforced plastic) isolation panels lower section 48" high
- 10 FRP (fiberglass reinforced plastic)** isolation panels 69.375" high x 36" long with 3/4" wide aluminum frame, for use as solid back panel
-with colored polyethylene grid top section 24" high
-with FRP (fiberglass reinforced plastic) isolation panels middle section 48" high
-with FRP (fiberglass reinforced plastic) isolation panels lower section 3" high
-with Door Opening - Large(29"x17"wide)
- 20 Composite UltraBase above floor unit 36" wide x 48" long*****
-with Rest bench**
- 20 Stainless Steel Gate Unit**
74" high x 36" long
-with all sections stainless steel wire grid
-with Stainless Steel two-way latch
-with bottom frame with Stainless Steel Double 2.5 qt. Bowl insert
-with bowl located on hinge side
- 20 Stainless Steel Mesh Top Cover**
36" high x 48" long
- 10 Large Poly-Metal panel mounted transfer door to fit opening up to 29 in. high by 17 in. wide**
-with channel length 69"
-with Weight Assisted Handle
-with Aluminum cable guard
-with one frame mounted pulley in place of standard pulley for use with Stainless steel Gates

Additional Specifications:

***FRP (fiberglass reinforced plastic) isolation panels:**

- Polypropylene fluted core panel construction (no natural fibers) will not absorb moisture
- Panels will not warp with changes in temperature
- USDA Certified antimicrobial surface is easy to clean and sanitize
- Aluminum framework is strong and rust-proof
- Patented Sani-Slope floor sealing system adjusts to various floor slopes

****Aluminum Frame Rest Bench:**

- The rest benches are made with the FRP.
- Sturdy aluminum frame
- Scratch-resistant surface
- Swing-up style
- Leg inserts reduce noise and protect kennel floors

*****Composite UltraBase above floor unit:**

- One-piece molded fiberglass base with a side radius that extends up to 6"there will be no floor-side seam to flex, crack or leak over time
- On floor PVC piping routes liquids and wastes to nearest sewer outlet
- Base attaches to side panels with watertight seal.
- Base features an anti-slip floor unit for safety and easy to clean procedures
- Base has adjustable legs to allow for installation on uneven floors. They can be installed as a stand-alone unit or series.